



Extended Reach Tool



11275 Windfern Rd. Ste. B
Houston, TX 77064
Phone: (281) 897-8600
Fax: (281) 897-8602

Website: www.kenjer.com
info@kenjer.com

Further, Faster

Streamline your operations by introducing Kenjer's new extended reach tool, the Krawler, into your BHA. In addition to producing oscillations axially along the length of tubing, the Krawler contains a proprietary device which also induces a gentle lateral vibration to further reduce friction near the bit.

Key Features

- 44.5" shoulder to shoulder length is amongst the shortest in the market
- Ability to provide friction reduction both locally and along the length of coil
- High flow rate capability

Technical Specifications*

Tool Size	Length (in.)	Weight (lbs)	Flow Rate (gpm)	Pressure Drop (psi)	Max Temp (deg F)	Frequency (hz)	Connection	Tensile Yield (lbf)	Torsional Yield (lb-ft)
3-1/8"	44.5	70	100-210	400-600	320	3.8 - 7.8	2-3/8" Reg.	127,000	3,700
2-7/8"	44.5	59	63-168	400-600	320	3.9 - 10.5	2-3/8" PAC	105,000	2,800

* These are theoretical values calculated that do not consider combined loading. An appropriate factor of safety should be used depending on conditions expected in the field. These values are true and accurate at the time of print date shown below. Information is subject to change without prior notice.
10/10/2018



